Design of an Experimentally Accessible Autonomous Medical Nanoagent: Computation, Sensing, Perturbations, and Locomotion via Motor Protein Signal Transmission.

By Colin Kakama

21 May 2026.

Abstract

This report presents a conceptual design framework for an autonomous medical nanoagent constructed primarily from cellulosic composite materials, with kinesin motor proteins serving as the mechanism for both power delivery and signal transmission. The design assumes the prior realisation of an advanced nanomanufacturing capability, described in earlier work by the author, that enables controllable polymerisation of glucose into discrete cellulose nanoparts with precise control over geometry, surface chemistry, and nanomechanical properties.

The architecture builds on Robert Freitas' chemomessenger cable concept. A signal propagation concept is proposed in which kinesin proteins walk along engineered tubulin filaments as discrete information carriers, with ATP concentration modulation defining binary “on” and “off” states. This same switching logic is extended to Boolean computation, where tubulin-motor protein assemblies function as transistor equivalents, enabling the construction of logic gates and, in principle, a full onboard CPU. Similarly, power and mechanical motion are generated and transmitted through regulated populations of motor proteins acting on cellulosic components, with geometric constraints used to convert that force output into task-specific motions.

Two sensing modalities are prioritised for experimental accessibility, Five locomotion modalities are identified including a novel nanorail concept and manipulation is classified. Finally, two agent classes are defined: communicytes, which serve as mobile data carriers and distributed processing nodes, and effector nanoagents, whose modular design is tailored to specific therapeutic or sensing interventions. The report concludes with illustrative deployment scenarios in antifibrotic therapy and neural interfacing.

Table of Contents

Abstract **1**
1. The Necessity of Advanced Nanomanufacturing **2**
2. Motor Proteins as a Main Power And Signal Source. **3**
3. Core Nanoagent Features **4**
3.1. Signal Transmission 4
3.2. Boolean Logic 5
3.2.1. Introduction to Boolean Logic, Logic Gates, ALUs, RAM, and CPUs 5
Boolean Logic and Logic Gates 5
RAM and Registers 6
CPUs: Logic Gates All the Way Down 7
3.2.2. Encoding Logic Using Motor Proteins 7
3.3. Power and Motion Generation/Transmission 9
3.4. Sensing 10
3.5. Locomotion 10
3.6. Manipulation 12
4. The Two Kinds of Nanoagents And Specific Design Considerations For Each. **12**
4.1. Communicytes 12
4.2. Effector Nanoagents 13
References **13**

1. The Necessity of Advanced Nanomanufacturing

As this report will demonstrate, current nanofabrication methods are insufficient to embed the degree of functionality required for truly autonomous nanomechanical agents. A non-trivial advance beyond conventional nanoassembly techniques must be realised before one can seriously consider constructing bioengineering agents that go beyond passive nanoparticles that are merely trafficked through cellular space and rely on environmental reactivity to perform their function.

In prior work, the author described a method of using a yet-to-be-demonstrated machine to controllably polymerise glucose molecules into discrete cellulose nanoparts [1][2][3], and explored the possibility of functionalising those manufactured nanoparts within mechanical nanosystems [4]. Precise control over cellulose synthesis at this level would confer equivalent control over nanopart geometry, nanomechanical properties, and surface chemistry.

This advanced nanomanufacturing capability is the necessary precursor to the technology explored in this report, and its eventual realisation is assumed as a foundation.

The nanoagents examined here are composed primarily of cellulose-derived shells and mechanical components that will, by the point of full system integration, incorporate dopant materials and functional additives. Therefore, ***cellulosic composite***[5] is a more accurate descriptor than pure cellulose. With that framing established, the report proceeds.

2. Motor Proteins as a Main Power And Signal Source.

Motor molecules are ones that when given an energy source, can produce discrete motion. This simple phenomenon gives one the ability to create both a mechanical power and signal generator which are the core tenets of a self-contained nanorobot[6].

Take the kinesin motor protein for example, which hydrolyses adenosine triphosphate (ATP) into adenosine diphosphate (ADP) and inorganic phosphate(P_i) to produce an internal structural change that then gives rise to a locomotive effect across the broader macro molecule. This process allows it to move across a microtubule track it is on[7] as figure 1 depicts.

Figure 1: Diagram illustrating motility of kinesin



image source: https://commons.wikimedia.org/w/index.php?curid=7823703

By using the advanced nano manufacturing techniques detailed in the previous chapter, one could fabricate tracks of tubulin and immobilise populations of kinesin molecules on. These kinesins can later be promoted or inhibited to locomote along the tubes by controlling the supply of ATP in a medium.

Other motor molecules may be considered for further iterations of such a platform but for this report, the well understood kinesin family will be explored.

3. Core Nanoagent Features

3.1. Signal Transmission

Robert Freitas, in *Nanomedicine* Chapter 7.2.5.5, introduced the concept of chemomessenger cables as a mechanism for intra-nanoagent signal transmission. He posited that one could transfer information using chemical messenger molecules confined within sealed conduits.

Building on this, one can extend the principle by applying the mechanics of kinesin motor proteins. Rather than passive chemical diffusion through a pipe, a signal highway can be constructed from tubulin filaments, with kinesin proteins walking along them as discrete information carriers. Supplemented by ATP reservoirs and pumps distributed along the highway to regulate kinesin activation, this architecture yields a viable signal propagation system capable of supporting both nanoprobe-to-nanoprobe communication and nanoprobe-to-macrocomputer communication.

Figure 2: Schematic: (1) nanoprobe-nanoprobe signalling; (2) nanoprobe-macrocomputer signalling, showing the pathway: nanoagent → signal amplifier/corrector/transformer → electrode → computer



Once a signal has been transmitted from one tubulin terminal to the next, the designer has two options for managing motor protein state:

1. The first is to reverse kinesin polarity, allowing the proteins to return along the filament. A behaviour demonstrated by *Nakamura et al.* where bursts of blue light and a photoactive protein domain were used to enable light-dependent conformational changes in an engineered lever arm of a kinesin molecule, allowing it to speed up, slow down or switch directions[8]
2. The second, simpler option is to restrict motion to a single direction and route the filament into a closed loop, keeping signalling kinesins in continuous unidirectional circulation.

Further, by modulating the speed or concentration of motor proteins traversing the cable, one can produce a waveform distribution of signal intensity. Threshold values for kinesin activation then define discrete on and off states and with that, transferable bits. This is the bridge to the following chapter which addresses nanoagent logic.

Figure 3: Signal distribution with labelled on/off states



3.2. Boolean Logic

3.2.1. Introduction to Boolean Logic, Logic Gates, ALUs, RAM, and CPUs

Boolean Logic and Logic Gates

Boolean algebra provides a formal framework for representing truth. Within it, variables take one either TRUE or FALSE values and three fundamental operations govern their manipulation: AND, OR, and NOT. From these, one can construct logical expressions of arbitrary complexity using standard truth tables.

Figure 4: truth tables for AND, OR and NOT gates.

AND

INPUT		OUTPUT
A	B	
0	0	0
1	0	0
0	1	0
1	1	1

OR

INPUT		OUTPUT
A	B	
0	0	0
1	0	1
0	1	1
1	1	1

NOT

INPUT	OUTPUT
A	
0	1
1	0

These three operations constitute the fundamental logic gates. From them, one can derive composite gates such as NAND (NOT-AND) and NOR (NOT-OR), and by combining gates of increasing complexity, one can construct a machine capable of evaluating arbitrary logical instructions. That machine is a computer.
Using only this framework, one can build an arithmetic logic unit (ALU) which is really a combination of two units: The arithmetic unit which is a collection of transistors handling numerical operations such as addition and subtraction. And the logic unit which is a parallel collection of transistors handling logical operations. Together they form the computational core of any processor.

RAM and Registers

Computing a value and discarding it is useless. The result must be stored, and in most cases many results must be held simultaneously so that multiple operations can be performed in parallel.
A circuit can be made to retain a previously received bit by routing certain logic gate outputs back into their own inputs, such that a stored value persists without change. This is the principle behind the AND-OR latch, and it is the basis of memory.

By organising transistors into a gated latch configuration and adding input and write-enable lines, one can continuously write data into and read data out of a memory cell. Scaling this up, a group of latches assembled together forms a register. Early computers used 8-bit registers but now, modern processors universally operate on 32-bit or 64-bit registers, with specialised processors extending to 128, 256, or 512 bits. Registers are a core building block of the CPU.

CPUs: Logic Gates All the Way Down

A CPU combines registers, an ALU, RAM, and a clock to perform computation. At the most reductive level, it is a very large number of transistors connected in carefully designed arrangements. The more transistors one has, and the more cleverly they are arranged, the greater the computational

capacity. With enough of them integrated together, one arrives at a processor: a device that can load values from memory, operate on them, and write results back.

The first commercial single-chip CPU was the Intel 4004, a 4-bit processor released in 1971.

Figure 5: Intel 4004 microarchitecture diagram.
Source: Crashscourse and PBS Digital Studios,
https://youtu.be/FZGugFqdr60?si=nmlLKrlG4BRoZzQ2



3.2.2. Encoding Logic Using Motor Proteins

In the context of a nanorobot computer, the functional equivalent of a transistor is a tubulin track with motor proteins travelling along it, housed within a protected internal cavity.

Each such transistor operates on an ATP concentration threshold. Below that threshold, very few motor proteins are biased toward movement. Above it, a significantly larger population migrates along the track. The on state is defined as the condition in which a critical number of motor proteins traverse the full length of a first tubulin tube and, upon reaching its terminal end, excite the initial end of a second tube.

Figure 6: On state and off state of motor protein switch.

Molecular Switch in “ON” State


1. ATP(in red) added to system
2. Activated motor proteins move to terminal end of tube 1
4. Dormant motor proteins awaiting ATP signal
tubulin track 1
tubulin track 2
ATP reserve & pump
Motor proteins are recycled
3. Motor protein presence activates ATP release for second tubulin track and propagating signal continues

Molecular Switch in “OFF” State


1. No ATP(in red) added to system
2. Little to no motor proteins activation
4. Dormant motor proteins awaiting ATP signal
tubulin track 1
tubulin track 2
ATP reserve & pump
3. No motor protein presence at tubular bridge and hence no secondary ATP release

For a single bit of information, ATP concentration is controlled by trigger-releasing a small quantity of ATP into the transistor cavity, inducing a burst of motor protein activation and migration. When the input from tube 1 is 1, the excitation propagates to the neighbouring tube. However, if ATP is not released and cavity concentration remains low, little to no motor protein migration occurs, no excitation is transmitted, and the output is 0.

Motor proteins that complete a cycle are looped back through a closed unidirectional circuit and recycled for subsequent cycles.

By chaining these tubulin-motor protein transistors together, one can construct the three fundamental logic gates, and from there build composite gates of increasing abstraction, up to and including a full CPU. This computer would be housed within one of the nanobot's internal cavities. When multiple nanobots communicate, they gain access to swarm intelligence: the capacity to share computational resources across agents.

Questions of transistor count, physical footprint, and achievable performance remain open and require rigorous theoretical treatment beyond the scope of this report. But general heuristics to keep in mind for anyone that wishes to derive these are the following:

1. Force generated by a single motor protein: 1.9 pN to 7.0 pN [16][17]
2. Speed of motor proteins: in vitro speed of 800 nm/s and an in vivo speed of 2000 nm/s. [18]
3. Size(volume) of motor protein: length of 10nm [19]
4. Size(diameter) of tubulin track: ~25nm wide [20]
5. Number of ATP molecules needed to perform one kinesin step motion: a single ATP molecule per 8 nm advance. [16][17]

3.3. Power and Motion Generation/Transmission

As established, ATP serves as the primary energy source for both power delivery and signal transmission throughout the nanoagent. Molecular reservoirs and injection pumps are distributed periodically across the system to maintain adequate local ATP concentrations at their respective sites of action.

Mechanical force is generated by populations of motor proteins acting collectively. Their aggregate output drives the tensile and compressive loading conditions that govern the tribological behaviour of the nanobot's cellulosic mechanical components during operation.

Modulating the local ATP concentration surrounding a given motor protein population is the principal means of varying mechanical output. By raising or lowering availability of the molecule at specific sites, the designer can tune force magnitude, actuation timing, and the broader kinematic behaviour of the mechanical system on demand.

Beyond direct motor protein output, auxiliary components can be incorporated to condition and redirect that force into specific useful forms. Molecular gears, static barriers, and geometric constraints can be arranged to introduce directional biases, attenuate or amplify force along a given axis, or convert linear motion into rotational or helical trajectories, among other configurations.

3.4. Sensing

There is no shortage of informatics and ways to extract them that are possible inside of cells. However, for an experimentally accessible nanoagent, two sensing modalities are of primary importance:

1. Chemosensing of cellular chemistry
2. Spatiotemporal sensing

For chemosensing, morphable receptors that cycle between distinct conformational states are the appropriate architecture. By switching shape at defined intervals, for instance once per second, a single receptor can sequentially recognise a library of molecules present in the local environment rather than being limited to a single target. This behaviour is analogous to that of allosteric receptors, which alter their response to a primary stimulus upon binding a secondary modulator at a distinct site [10]. Applied here, the same principle allows the nanoagent to build a chemoinformatic map of its immediate surroundings across multiple molecular species over time.

For spatiotemporal sensing, distance between nanoagents can be inferred by measuring the transit time of a signal travelling from one agent to another. When this is combined with the chemoinformatic data being continuously gathered, near real-time estimates of position and orientation within the cell become achievable.

For more exhaustive treatment of nanorobot sensing modalities relevant to future iterations of this design, Chapter 4 of Freitas' Nanomedicine is the appropriate reference.

3.5. Locomotion

Active movement through tissue and cell space is a basic capability common to all theorised nanorobotic interventions. It is, in many respects, the central pillar around which other functional subsystems are organised. Popular depictions of medical nanorobots as miniature vehicles traversing cell membranes and receptor surfaces, while simplified, do capture the essence of this requirement.

The key locomotion modalities relevant to this report are as follows:

1. **Cytoambulation (surface walking):** The traversal of nanoscopic robots across cellular surfaces within the body, including the endothelial walls of blood vessels, mucous membranes lining the respiratory tract, and fibrous membranes of connective tissue [11].
2. **Histonatation (swimming):** Locomotion through biological tissues via swimming-type motion [12].
3. **Cytopenetration (cell entry):** The passage of a nanorobot through a cell's plasma membrane without inflicting lethal damage to the host cell [13].
4. **In-cyto locomotion (intracellular navigation):** Locomotion exclusively within the intracellular environment. This is when a nanoprobe navigates the cluttered, highly viscous cytomatrix [14].
5. **Cytocarriage (assisted transport):** As originally defined by Freitas, this involves a nanorobot attaching to a cell and chemically or mechanically steering it toward a target destination. For the purposes of this report, the definition is extended to include hitching transport on other biological agents such as organelles and protein aggregates. This would allow the body's existing transport infrastructure to do a portion of the locomotion work.

Nanoagents would be equipped with appendages enabling these various locomotion modes. One such example is locomotion via tubulin track riding. Freitas briefly describes this in Chapter 9.4.6,

envisaging nanorobots hooking onto existing cytoskeletal filaments for motility. The present design extends this concept further. Equipping select nanorobots with onboard machinery capable of continuously polymerising tubulin would allow those agents to lay tracks in real time, on which other nanorobots can mechanically attach to and ride in the manner of a cable car on a rail.

Figure 7: Cable car on rail, for analogy

Multiple branches of these nanorails could be spun up by dedicated **track-laying bots**, providing a dynamic transport infrastructure along which nano and microscale agents can move rapidly, both extracellularly and intracellularly.

This approach has a natural precedent in biology. Certain pathogens exploit a mechanistically similar strategy for their own motility, in a process known as *actin-based motility*. Pathogens such as *Listeria monocytogenes* activate components of the host cell's actin assembly machinery to nucleate the formation of actin tails on their own surface. The continuous polymerisation of these tails generates a propulsive force that drives the organism through the cytoplasm and subsequently into adjacent cells[15]. The nanorail concept draws on the same underlying logic of using tubes and motor proteins and transport.

Other theoretical approaches to appendage design, drawing on canonical cellular phenomena as inspiration, are described in detail in Freitas' *Nanomedicine*, Chapter 9.4.

3.6. Manipulation

Manipulation can be broken down into two broad categories:

1. **Indirect:** Carrying chemical reagents within onboard reservoirs and releasing them at target sites.

2. **Direct:** Using appendages of the kind described above, along with function-specific effectors, to perform mechanical and chemical perturbations on cellular structures. A representative example is a metamorphic screw drive designed for cytopenetration.

Figure 8: Metamorphic screw drive for cytopenetration.

Source: Freitas, Nanomedicine, Fig. 9.29, Chapter 9.4.5.1



4. The Two Kinds of Nanoagents And Specific Design Considerations For Each.

4.1. Communicytes

Communicytes are mobile mass-storage devices conceived within the molecular nanotechnology literature. Their primary role is that of a postal carrier: collecting data payloads from stationary nanorobots and transporting that information to other regions of the body for processing or external communication.

Alongside perturbation-focused nanorobots, communicytes play a critical role in ensuring that informatics are not only collected but actively processed in a distributed manner. Equipping them with onboard storage and computing units extends their utility well beyond simple data ferrying. In this configuration, they function analogously to distributed data centres, forming the mesh network layer responsible for background processing and data routing that underpins the broader nanobot operation.

4.2. Effector Nanoagents

These agents fulfil the roles described in the manipulation chapter of this report. Their design is modular by necessity: the accessories and effectors they carry are selected based on the specific intervention they are deployed for.

Two illustrative examples:

1. **Antifibrotic therapy:** Nanorobots tasked with treating fibrosis would be equipped to identify and latch onto epithelial cells, penetrate into their intracellular space, and denature the fibrous proteins responsible for the disease.
2. **Brain-computer interface:** Nanorobots deployed for neural interfacing would be equipped to selectively identify and bind to specific neuron types, discriminating against non-target cells, and insert probes through the membrane to measure intracellular activity including molecular transport and the local status at each probe insertion site.

A more precise taxonomy for this class of agent is left for future iterations of this design framework.

References

1. Kakama C, **Using a Cascade of Molecular Reactor Cages as a Nanomanufacturing Platform**, Substack: https://open.substack.com/pub/colinyaps/p/using-a-cascade-of-molecular-reactor?r=1yq3uz&utm_campaign=post&utm_medium=web&showWelcomeOnShare=true
2. **Literature Validation Of A Cascading Molecular Reactor Cage Architecture For A Molecular Manufacturing Device**. By Colin Kakama: https://archive.org/details/literature-validation-of-a-cascading-molecular-reactor-cage-architecture-for-a-m
3. **Schematic of cellulose nano 3d printer:** https://colinkakama.bearblog.dev/schematic-of-cellulose-nano-3d-printer/
4. Kakama C, **Design Parameters And Performance Limits For A Nanomolding Nanoassembly Self Contained Manufacturing Platform**, by Colin Kakama: https://archive.org/details/design-parameters-and-performance-limits-for-a-nanomolding-nanoassembly-nanofact
5. Cellulosic: https://www.merriam-webster.com/dictionary/cellulosic
6. **Nanomedicine, volume I: Basic capabilities** by Robert A. Freitas Jr. ISBN 1-57059-645-X
7. Kinesin, Wikipedia, https://en.wikipedia.org/wiki/Kinesin
8. Nakamura et al., **Remote control of myosin and kinesin motors using light-activated gearshifting**, Nature Nanotechnology, 2014 | DOI: 10.1038/NNANO.2014.147
9. This is the most comprehensive, while being accessible introduction to motor proteins I have found: Youtube: **Ron Vale (UCSF, HHMI) 1: Molecular Motor Proteins**: https://youtu.be/9RUHJhskW00?si=EZTe5VQEbyOE2O0h
10. **Allosteric modulators**, Wikipedia, https://en.wikipedia.org/wiki/Allosteric_modulator
11. Freitas Nanomedicine, 9.4.3
12. Freitas Nanomedicine, 9.4.4

13. Freitas Nanomedicine, 9.4.5
14. Freitas Nanomedicine, 9.4.6
15. Goldberg MB. 2001. **Actin-Based Motility of Intracellular Microbial Pathogens**. Microbiol Mol Biol Rev 65:https://doi.org/10.1128/mmbr.65.4.595-626.2001
16. Scot C. Kuo, Michael P. Sheetz ,**Force of Single Kinesin Molecules Measured with Optical Tweezers**.Science260,232-234(1993).DOI:10.1126/science.8469975
17. Visscher, K., Schnitzer, M. & Block, S. S**ingle kinesin molecules studied with a molecular force clamp**. Nature 400, 184–189 (1999). https://doi.org/10.1038/22146
18. BioNumbers, How fast do molecular motors move on cytoskeletal filaments?: https://book.bionumbers.org/how-fast-do-molecular-motors-move-on-cytoskeletal-filaments/
19. Bionumbers: https://bionumbers.hms.harvard.edu/bionumber.aspx?s=n&v=1&id=109238
20. Microtubule, wikipedia, https://en.wikipedia.org/wiki/Microtubule